

Face Construction	IMPERIAL	METRIC	TEST METHOD
CONSTRUCTION	Stratatec® Patterned Loop		
Gauge	5/64	50.4 rows/10 cm	
Stitches per Inch	9.2	36.2 pu/10 cm	ASTM D-418, Sec. 12
Pile Height Average	0.187 inch	4.7 mm	ASTM D-418, Sec. 12
Fiber System	Dynex® Nylon		
Dye Method	Yarn Dyed		
Soil/Stain Protection	Ensure	10.9 Kilotex	

### Color Line

23001 Obi	23007 Buckwheat	23013 Bonsai	23019 Bluefin
23002 Curry	23008 Bamboo	23014 Wasabi	23020 Pacific
23003 Maple	23009 Shitake	23015 Cypress	23021 Moonlight
23004 Azalea	23010 Matcha	23016 Nori	23022 Ink
23005 Red Cedar	23011 Miso	23017 Oolong	23023 Wisteria
23006 Ginger	23012 Soba	23018 Watercress	23024 Dark Cloud

### Product Testing/Information

Surface Flammability	Passes CPSC FF 1-70	(ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher)	(ASTM E-648)
Electrostatic Propensity	3.0 kV or lower Permanent Conductive Fiber	(AATCC 134)
Primary Tufting Substrate	Synthetic Non-Woven	
RS Adhesive System	Microencapsulated Tackifier applied during manufacturing	

### Installation Notes

Random

### Product Notes

- C&A products meet the flammability requirements for the following nationally recognized building codes: BOCA National Building Code, NFPA Life Safety Code for Safety to Life in Buildings and Structures, Standard Building Code, and the Uniform Fire Code.
- Product specifications reflect mean averages based on tests of production runs by independent laboratories and may vary within normal industry and standardized testing tolerances. Colors may vary slightly from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements become available which provide for improvements of the product's performance, but will not decrease product's overall recycled content or the recyclability of the product.
- C&A has a carpet collection / recovery system and a currently operational, commercial scale, recycling process to recycle vinyl backed carpet. Carpet recycled in the process is used to produce recycled content carpet. C&A Floorcoverings' products, when recovered are 100% recyclable in this process.
- Recycled Content has been third part certified by Scientific Certification Systems. Exact percentages vary by style. Percentage ranges of overall recycled content include post consumer content.
  - ethos™ Products: 36 - 52%; Min. 10% post consumer.
  - ER3® C-10 Roll Products: 36 - 52%; 10% post consumer.
  - ER3® Modular Tile Products: 44 - 59%; 10% post consumer.
- Products have received the following Environmentally Preferable Product Certifications:
  - ethos™ Products: Platinum EPP (NSF-140); California Platnum (California Gold Standard)
  - ER3® C-10 Roll Products: Gold EPP (NSF-140); California Gold (California Gold Standard)
  - ER3® Modular Tile Products: Platinum EPP (NSF-140); California Platnum (California Gold Standard)
- U.S. Patent numbers: 4,849,297; 4,849,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574
- The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive direct maintenance will be required for areas in contact with chair caster traffic, and some degree of appearance change is to be expected.

For additional information please visit [www.tandus.com/warranties](http://www.tandus.com/warranties), [www.tandus.com/maintenance](http://www.tandus.com/maintenance), or [www.tandus.com/specifications](http://www.tandus.com/specifications)

311 Smith Industrial Boulevard Post Office Box 1447 Dalton, Georgia 30722-1447 800.248.2878 [tandus.com](http://tandus.com)

IMPERIAL		METRIC		TEST METHOD	
<b>ER3® RS® Modular Tile / ER3® Modular Tile (SCS Certified, Environmentally Preferable Product) *GLP1366</b>					
Product Size	24" x 24" Tile		60.9 cm x 60.9 cm		
Tru Bloc	High Density Polymeric Barrier System				
Backing	100% Recycled Content				
Density (ASTM D-1667)	65	lbs/cu ft	1041	kg/cu m	
Total Weight RS / Non-RS	132.5	130.9	oz/sq yd +/- 5%	4492	4438 g/sq cm
Total Product Recycled Content	51.7%		Post Consumer : 10%		
EPP Certification	Platinum EPP (NSF-140); California Platinum (California Gold Standard)				
Warranty: 15 year non-prorated limited warranty against excessive surface wear and static, delamination, edge ravel, zippering, and backing resiliency loss.					



<b>Flex-Aire™ RS® Cushion Tile / Flex-Aire™ Cushion Tile *GLP6558</b>					
Product Size	24" x 24" Tile		60.9 cm x 60.9 cm		
Tru Bloc	High Density Polymeric Barrier System				
Backing	Fiberglass Reinforced Composite Closed Cell Vinyl Cushion				
Weight	35.5	oz/sq yd	1203	g/sq m	ASTM D-1667
Density	18.5	lbs/cu ft	296	kg/cu m	ASTM D-1667
Thickness	0.156	inch	3.96	mm	ASTM D-1667
Total Weight RS / Non-RS	122.0	119.7	oz/sq yd +/- 5%	4137	4059 g/sq m
Total Product Recycled Content	18.4%				
Compression Set	Max. 10%				ASTM D-1667
Compression Deflection	5 min.	25 max lbs/sq inch @ 25%	352	1758	g/sq cm ASTM D-1667
Warranty: 15 year non-prorated limited warranty against excessive surface wear and static, delamination, edge ravel, zippering, and backing resiliency loss.					

<b>Conserv Modular Tile *GLP4173</b>					
Product Size	24" x 24" Tile		60.9 cm x 60.9 cm		
Backing	Thermoplastic Polymeric				
Density (ASTM D-1667)	120	lbs/cu ft	1041	kg/cu m	
Total Weight Non-RS	99.24	oz/sq yd +/- 5%	3364	g/sq cm	
Warranty: 15 year non-prorated limited warranty against excessive surface wear and static, delamination, edge ravel, zippering, and backing resiliency loss.					

C&A Floorcoverings, A Tandus™ Company

311 Smith Industrial Boulevard Post Office Box 1447 Dalton, Georgia 30722-1447 800.248.2878 tandus.com

\*GLP = CRI Green Label Plus Certification Number

Effective 10/08