

Description	Textured Loop Pile Carpet Tile	
Origin	Manufactured in the UK	
Pile Fibre	100% Antron Lumena Nylon	
Dye Method	Solution Dyed	
Method of Manufacture	Tufted	
Machine Gauge	1/12th (47 stitches per 10 cm)	
Pile Weight	650 g m ²	
Tufts per m ²	211,500 tufts per m ²	
Pile Height	2.9 mm	
Total Thickness	5.8 mm	
Total Weight	4,075 g m ²	
Secondary Backing	Modified Bitumen	
Wear Class Luxury Class	Class 33 Heavy Commercial Use LC2	EN 1307
Castor Chair Rating	≥ 2.4r (2.9r) Continuous Use	EN 985
Impact Sound Reduction	ΔLw 22 dB	EN ISO 10140
Sound Absorption	α _w 0.15	EN ISO 11654
Thermal Insulation	0.17 m ² kW	ISO 8302
Electrostatic Properties	≤ 2 kV (Antistatic)	ISO 6356
Flammability Rating	B _{FL} -S1	EN 13501
Electrical Resistance	Horizontal	1.7 x 10 ¹⁰ Ohm
	Vertical	4.7 x 10 ⁹ Ohm
Colourfastness to Light	≥ 6 (on a scale of 1-8)	ISO 105-B02
Stock Profile	Stocked in the UK	
Standard Sizes	500 mm x 500 mm	
Pack Sizes	20 per Carton (5 m ²)	
Installation Methods	Loose Lay (Brick or Non-Directional)	
Approximate Lead Times	Ex-stock 48 hours Ex-production 6-8 weeks	

