

PURE WOVEN VINYL

PRODUCT SPECIFICATION
ISSUE 2019-V1



Ranges		Bold Brave Fair Gentle Noble Sharp Wild	
Description		Woven Vinyl Tile & Sheet	
Origin		Manufactured in Belgium	
Pile Fibre		PVC Yarn with Glass Fibre Core	
Method of Manufacture		Woven	
Total Thickness	Tile	3.3 mm	
	Sheet	2.5 mm	
Total Weight	Tile	4,500 g m ²	
	Sheet	2,500 g m ²	
Secondary Backing		Phthalate-free PVC	
Wear Class		Class 33 Heavy Commercial Use	EN 1307
Castor Chair Rating		≥ 2.4r Continuous Use	EN 985
Impact Sound Reduction	Tile	ΔLw 14 dB	EN ISO 10140
	Sheet	ΔLw 12 dB	
Sound Absorption		α _s 0.05	EN ISO 11654
Thermal Insulation		0.20 m ² KW Suitable for Underfloor Heating	ISO 8302
Electrostatic Properties		≤ 2 kV Antistatic	ISO 6356
Flammability Rating		B _{FL} -S1	EN 13501
Colourfastness to Light		≥ 7 (on a scale of 1-8)	ISO 105-B02
Slip Resistance	Dry Slip Potential	DS Non-slip	EN 13893
Emissions Certifications		Meets BREEAM GN22 V2.3 Exemplary Level Criteria	
Stock Profile	Tile	Selected Colours Stocked in the EU, Other Colours Made-to-Order Min Qty 50 m ²	
	Sheet	Made-to-Order Min Qty 50 m ²	
Product Sizes	Tile	500 mm x 500 mm	
	Sheet	2 m wide	
Pack Sizes	Tile	16 per Carton (4 m ²)	
	Sheet	appr 25 1m Rolls (50 m ²)	
Installation Methods	Tile	Loose Lay (Ashlar or Quarter Turn)	
	Sheet	Direct Stick	
Recommended Adhesives	Tile	Ntgrate Tackifier	
	Sheet	Ntgrate Permanent	
Approximate Lead Times		Ex-stock EU 2 weeks Ex-production 4-6 weeks	

