

WHISPER WOVEN VINYL

PRODUCT SPECIFICATION
ISSUE 2019-V1



| | | |
|--------------------------|--|---------------|
| Ranges | Bold Brave Fair Gentle Noble Sharp Wild | |
| Description | Woven Vinyl Sheet | |
| Origin | Manufactured in Belgium | |
| Pile Fibre | PVC Yarn with Glass Fibre Core | |
| Method of Manufacture | Woven | |
| Total Thickness | 3.5 mm | |
| Total Weight | 2,200 g m ² | |
| Secondary Backing | Phthalate-free Blown PVC | |
| | | |
| Wear Class | Class 32 Moderate Commercial Use | EN 1307 |
| Castor Chair Rating | ≥ 2.4r Continuous Use | EN 985 |
| Impact Sound Reduction | ΔLw 20 dB | EN ISO 10140 |
| Sound Absorption | α _s 0.05 | EN ISO 11654 |
| Thermal Insulation | ≤ 0.15 m ² KW Suitable for Underfloor Heating | ISO 8302 |
| Electrostatic Properties | ≤ 2 kV Antistatic | ISO 6356 |
| Flammability Rating | B _{FL} -S1 | EN 13501 |
| Colourfastness to Light | ≥ 7 (on a scale of 1-8) | ISO 105-B02 |
| Slip Resistance | Dry Slip Potential | DS Non-slip |
| | | |
| Emissions Certifications | Meets BREEAM GN22 V2.3 Exemplary Level Criteria | |
| | | |
| Stock Profile | Made-to-Order Minimum Order Quantity 50 m ² | |
| Roll Width | 2 m wide | |
| Roll Length | appr 25 1m Rolls (50 m ²) | |
| Installation Methods | Direct Stick | |
| Recommended Adhesives | Ntgrate Permanent | |
| Approximate Lead Times | Ex-production 4-6 weeks | |

