



SALTO 55 | SALTO 55 ACOUSTIC

PRODUCT SPECIFICATION
ISSUE 2019-V1



Description		Loose-Lay LVT Tiles & Planks	
Composition	Wear Layer	0.55 mm Textured UV Cured Polyurethane Varnish	
	Decorative Layer	HD Print Film	
	Core & Backing (Standard)	Phthalate-free & Recyclable PVC	
	Core & Backing (Acoustic)	Phthalate-free & Recyclable PVC with Foam Underlay	
Total Thickness		5.0 mm	
Total Weight	Standard	8,100 g m ²	
	Acoustic	6,400 g m ²	
Wear Class		Class 33 Heavy Commercial Use Class 42 General Industrial Use	EN 1307
Castor Chair Suitability		≥ 2.4r Suitable for Continuous Use	EN 4918
Residual Indentation	Standard	≤ 0.10 mm	EN 24343
	Acoustic	≤ 0.20 mm	
Impact Sound Reduction	Standard	ΔLw 7 dB	EN 717-2 10140-3
	Acoustic	ΔLw 19 dB	
Electrostatic Properties		≤ 2 kV Antistatic	EN 1815
Flammability Rating		B _{FL} -S1	EN 13501
Thermal Insulation	Standard	0.0187 m ² KW Suitable for Underfloor Heating	EN 12664
	Acoustic	0.0390 m ² KW Suitable for Underfloor Heating	
Slip Resistance	Dry Slip Potential	R9	DIN 51130
		≥ 0.30 DS (Non-Slip)	EN 13893
Light Fastness		≥ 7 (on a scale of 1-8)	ISO 105-B02
Environmental Product Declaration		SCS-EPD-03633	ISO 14025 EN 15804
Emissions Certification		A ⁺ Extremely Low (on a scale of A ⁺ -C)	EN 16000-6
Formaldehyde Emissions		Undetectable	EN 16000-3
Stock Profile		Stocked in the UK & EU	
Product & Pack Sizes	Tiles	500 mm x 500 mm	10 Tiles 2.5 m ²
	Planks	1200 mm x 180 mm	10 Planks 2.16 m ²
Approximate Lead Times		Ex-stock UK 48 hours Ex-stock Factory 2 weeks Ex-production 8-10 weeks	
Installation Type		Loose Lay on Tackifier Adhesive	
Adhesive Recommendations		F Ball F41 Mapei Ultrabond Eco-Tack Uzin U2100	
Installation Options		We Recommend: <ul style="list-style-type: none"> • Monolithic • Variable Drop 	

