



Product Specifications

Collection	Flat Weave Collection		
Description	Woven Contract Bouclé		
Pile Fibre	100% Nylon		
Dye Method	Continuous Dyed		
Method of Manufacture	Woven		
Pile Weight	785 g m ²		
Lead Time	Ex-Stock 2 Weeks Ex-Production 4-6 Weeks		
Format		Broadloom (texBAC-FW)	Acoustic Broadloom (feltBAC-FW)
Backing Type		texBAC-FW	feltBAC-FW
Backing		Woven Synthetic Textile	800 g m ² Recycled Felt
Pile Height		2.0 mm	2.0 mm
Total Thickness		4.0 mm	8.0 mm
Total Weight		2,400 g m ²	3,070 g m ²
Product Size		4 m	4 m
Pack Size		Std Roll Length +/-28 Im	Std Roll Length +/-20 Im
Availability		Stocked	Made-to-Order
Minimum Order Quantity		20 m ²	400 m ²
Installation Method		Direct Stick (Permanent)	Direct Stick (Permanent)
Recommended Adhesives	F Ball & Co	F3 F30	F3 F30
	Uzin	UZ 57 KE 2560	KE 2560

Performance Specifications

Format		Broadloom (texBAC-FW)	Acoustic Broadloom (feltBAC-FW)
Wear Rating	EN 1307	33 Heavy Commercial Use	33 Heavy Commercial Use
Flammability Rating	EN 13501-1:2020	C _{FL} S1	C _{FL} S1
Impact Sound Insulation	EN ISO 10140	ΔLw 17 dB	ΔLw 26 dB
Sound Absorption	EN ISO 11654	αw 0.15	αw 0.10
Thermal Resistance	EN 12667:2001	0.1 m ² kW Suitable for UFH	
Electrostatic Properties	EN ISO 6356	≤ 2 kV Antistatic	≤ 2.0 kV Antistatic
VOC Emissions	Indoor Air Comfort	Gold	Gold
	BREEAM GN22 v2.3 2018	Meets Exemplary Criteria	Meets Exemplary Criteria
EPD	ISO 14025 EN 15804	EPD-BEN-20160108-CBC1-EN	
Declaration of Performance	EN 14041	2531-CPR-CXA10207	2531-CPR-CXA10115

Additional Information

For a minimum quantity of 400 m² this product can also be supplied as 300 g|m² & 400 g|m² felt-backed Broadloom.