

Product Specifications

<i>Collection</i>	Flat Weave Collection		
<i>Description</i>	Woven Contract Bouclé		
<i>Pile Fibre</i>	100% Nylon		
<i>Dye Method</i>	Continuous Dyed		
<i>Method of Manufacture</i>	Woven		
<i>Pile Weight</i>	630 g m ²		
<i>Lead Time</i>	Ex-Stock 2 Weeks Ex-Production 4-6 Weeks		
<i>Format</i>	Tiles (feltBAC)	Broadloom (texBAC-FW)	
<i>Backing</i>	350 g m ² Recycled Felt	Woven Synthetic Textile	
<i>Pile Height</i>	2.0 mm	2.0 mm	
<i>Total Thickness</i>	5.0 mm	3.5 mm	
<i>Total Weight</i>	2,800 g m ²	2,000 g m ²	
<i>Product Size</i>	480 mm x 480 mm	4 m	
<i>Pack Size</i>	22 Tiles 5.07 m ² per box	Std Roll Length +/-28 lm	
<i>Availability</i>	Stocked	Stocked	
<i>Minimum Order Quantity</i>	1 box 5.07 m ²	20 m ²	
<i>Laying Pattern</i>	Monolithic		
<i>Installation Method</i>	Loose-Lay on Tackifier	Direct Stick (Permanent)	
<i>Recommended Adhesives</i>	<i>F Ball & Co</i>	F41	F3
	<i>Uzin</i>	Universal Tackifier	UZ 57 KE 2560

Performance Specifications

<i>Format</i>		Tiles (feltBAC)	Broadloom (texBAC-FW)
<i>Wear Rating</i>	<i>EN 1307</i>	33 Heavy Commercial Use	33 Heavy Commercial Use
<i>Flammability Rating</i>	<i>EN 13501-1:2020</i>	C _{FL} S1	C _{FL} S1
<i>Impact Sound Insulation</i>	<i>EN ISO 10140</i>	ΔLw 18 dB	ΔLw 17 dB
<i>Sound Absorption</i>	<i>EN ISO 11654</i>	αw 0.20	αw 0.15
<i>Thermal Resistance</i>	<i>EN 12667:2001</i>	0.1 m ² kW Suitable for UFH	0.1 m ² kW Suitable for UFH
<i>Electrostatic Properties</i>	<i>EN ISO 6356</i>	≤ 2 kV Antistatic	≤ 2 kV Antistatic
<i>VOC Emissions</i>	<i>Indoor Air Comfort</i>	Gold	Gold
	<i>BREEAM GN22 v2.3 2018</i>	Meets Exemplary Criteria	Meets Exemplary Criteria
<i>EPD</i>	<i>ISO 14025 EN 15804</i>	BEN-20170207-CBD1-EN	

Additional Information

For a minimum quantity of 40 boxes (202.80 m²) this product can be supplied in the following sizes: 240mmx960mm, 480mmx960mm, 960mmx960mm.

For a minimum quantity of 400 m² this product can also be supplied as 300 g|m², 400 g|m² or 800 g|m² felt-backed Broadloom.