



Product Specifications		
Format		Engineered Planks (wiseBAC)
Collection		Climate+ Collection
Description		Commercial Cork Flooring
Construction	Wear Layer	Highly Elastic Non-PVC Resin
	Decorative Layer	Cork Veneer
	Sub-surface	Agglomerated Cork
	Core	PVC-Free Cork Rigid Core
	Underlay	Integrated Cork Underlay
Total Thickness		7.0 mm
Edge Finish		Micro-bevel on all 4 sides
Product Size		1225 mm x 190 mm
Pack Size		8 Planks   1.862 m <sup>2</sup>
Availability		Stocked
Minimum Order Quantity		1 Box   1.862 m <sup>2</sup>
Installation Method	Standard:	Floating: Fold & Click
	Optional:	Glue Down: Fold, Click & Glue
Recommended Adhesives	F Ball & Co	B 92
	Uzin	MK 92 S
Lead Time		Ex-Stock 3 Weeks   Ex-Production 6-8 Weeks

Performance Specifications		
Format		Engineered Planks (wiseBAC)
Wear Rating	EN 1307	33   Heavy Commercial Use
Castor Chair Resistance	EN 425	≥ 2.4r   Continuous Use
Effect of Furniture Leg	ISO 16581   EN 424	No Visible Change or Damage
Impact Resistance	EN 13329:2006	≥ 1600
Flammability Rating	EN 13501-1:2020	B <sub>FL</sub> S1
Impact Sound Insulation	EN ISO 10140	ΔL <sub>w</sub> 18 dB
	EN 13893:2003	Class DS
	BS 7976-2:2002   Dry	μ 0.67   Low Slip Potential
Slip Resistance	BS 7976-2:2002   Wet	μ 0.54   Low Slip Potential
Formaldehyde Emissions	EN 717-1	E1
Content of Pentachlorophenol (PCP)	EN 14041 Annex B	Undetectable
Thermal Resistance	EN 12667:2001	0.06 m <sup>2</sup> kW   Suitable for UFH
Stain Resistance	EN 438-2 Group 1 Only 10 min	Grade 5   No Change
VOC Emissions	TÜV Proficert	Premium   Meets BREEAM Exemplary Criteria
BREEAM Potential Credits	Indoor Air Quality	1 to 5
	Designing for Durability and Resilience	1
	Material Efficiency	1
LEED v.4 Potential Credits	Low-Emitting Materials	1 to 3
	Indoor Air Quality Assessment	1 to 2