



Product Specifications

Collection	Flat Weave Collection		
Description	Woven Contract Bouclé		
Pile Fibre	100% Nylon		
Dye Method	Continuous Dyed		
Method of Manufacture	Woven		
Pile Weight	500 g m ²		
Lead Time	Ex-Stock 2 Weeks Ex-Production 4-6 Weeks		
Format	Tiles (feltBAC)	Broadloom (texBAC-FW)	Acoustic B'loom (feltBAC-FW)
Backing	350 g m ² Recycled Felt	Woven Synthetic Textile	800 g m ² Recycled Felt
Pile Height	2.0 mm	2.0 mm	2.0 mm
Total Thickness	5.0 mm	3.5 mm	8.0 mm
Total Weight	2,800 g m ²	2,100 g m ²	2,770 g m ²
Product Size	480 mm x 480 mm	4 m	4 m
Pack Size	22 Tiles 5.07 m ² per box	Std Roll Length +/-28 lm	Std Roll Length +/-20 lm
Availability	Stocked	Stocked	Made-to-Order
Minimum Order Quantity	1 box 5.07 m ²	20 m ²	400 m ²
Laying Pattern	<i>Epsilon Tweed & Uni</i>	Monolithic	
	<i>Epsilon Line</i>	Quarter Turn	
Installation Method		Loose-Lay on Tackifier	Direct Stick (Permanent)
Recommended Adhesives	<i>F Ball & Co</i>	F41	F3 F30
	<i>Uzin</i>	Universal Tackifier	UZ 57 KE 2560

Performance Specifications

Format		Tiles (feltBAC)	Broadloom (texBAC-FW)	Acoustic B'loom (feltBAC-FW)
Wear Rating	EN 1307	33 Heavy Commercial Use	33 Heavy Commercial Use	33 Heavy Commercial Use
Flammability Rating	EN 13501-1:2020	C _{FL} S1	C _{FL} S1	C _{FL} S1
Impact Sound Insulation	EN ISO 10140	ΔLw 18 dB	ΔLw 17 dB	ΔLw 26 dB
Sound Absorption	EN ISO 11654	αw 0.20	αw 0.15	αw 0.10
Thermal Resistance	EN 12667:2001	0.1 m ² kW Suitable for UFH	0.1 m ² kW Suitable for UFH	
Electrostatic Properties	EN ISO 6356	≤ 1.5 kV Antistatic	≤ 1.5 kV Antistatic	≤ 1.5 kV Antistatic
VOC Emissions	<i>Indoor Air Comfort</i>	Gold	Gold	Gold
	<i>BREEAM GN22 v2.3 2018</i>	Meets Exemplary Criteria	Meets Exemplary Criteria	Meets Exemplary Criteria
EPD	ISO 14025 EN 15804	BEN-20170208-CBD1-EN	BEN-20160089-CBC1-EN	
Declaration of Performance	EN 14041	2531-CPR-CXA10217	2531-CPR-CXA10183	2531-CPR-CXA10199

Additional Information

For a minimum quantity of 40 boxes (202.80 m²) this product can be supplied in the following sizes: 240mmx960mm, 480mmx960mm, 960mmx960mm.

For a minimum quantity of 400 m² this product can also be supplied as 300 g|m² or 400 g|m² felt-backed Broadloom.