



Product Specifications

| | | | |
|------------------------|--|------------------------------------|----------|
| Collection | Flat Weave Collection | | |
| Description | Woven Contract Bouclé | | |
| Pile Fibre | 100% Nylon | | |
| Dye Method | Continuous Dyed | | |
| Method of Manufacture | Woven | | |
| Pile Weight | 850 g m ² | | |
| Lead Time | Ex-Stock 2 Weeks Ex-Production 4-6 Weeks | | |
| Format | Broadloom (texBAC-FW) | Acoustic Broadloom (feltBAC-FW) | |
| Backing | Woven Synthetic Textile | 800 g m ² Recycled Felt | |
| Pile Height | 2.5 mm | 2.5 mm | |
| Total Thickness | 4.5 mm | 8.0 mm | |
| Total Weight | 2,500 g m ² | 3,070 g m ² | |
| Product Size | 4 m | 4 m | |
| Pack Size | Std Roll Length +/-28 lm | Std Roll Length +/-20 lm | |
| Availability | Stocked | Made-to-Order | |
| Minimum Order Quantity | 20 m ² | 400 m ² | |
| Installation Method | Direct Stick (Permanent) | Direct Stick (Permanent) | |
| Recommended Adhesives | <i>F Ball & Co</i> | F3 F30 | F3 F30 |
| | <i>Uzin</i> | UZ 57 KE 2560 | KE 2560 |

Performance Specifications

| | | | |
|----------------------------|------------------------------|--|---------------------------------|
| Format | | Broadloom (texBAC-FW) | Acoustic Broadloom (feltBAC-FW) |
| Wear Rating | <i>EN 1307</i> | 33 Heavy Commercial Use | 33 Heavy Commercial Use |
| Flammability Rating | <i>EN 13501-1:2020</i> | C _{FL} S1 | C _{FL} S1 |
| Impact Sound Insulation | <i>EN ISO 10140</i> | ΔLw 17 dB | ΔLw 26 dB |
| Sound Absorption | <i>EN ISO 11654</i> | αw 0.15 | αw 0.10 |
| Thermal Resistance | <i>EN 12667:2001</i> | 0.1 m ² kW Suitable for UFH | |
| Electrostatic Properties | <i>EN ISO 6356</i> | ≤ 2 kV Antistatic | ≤ 2.0 kV Antistatic |
| VOC Emissions | <i>Indoor Air Comfort</i> | Gold | Gold |
| | <i>BREEAM GN22 v2.3 2018</i> | Meets Exemplary Criteria | Meets Exemplary Criteria |
| EPD | <i>ISO 14025 EN 15804</i> | EPD-BEN-20160108-CBC1-EN | |
| Declaration of Performance | <i>EN 14041</i> | 2531-CPR-CXA10207 | 2531-CPR-CXA10115 |

Additional Information

For a minimum quantity of 400 m² this product can also be supplied as 300 g|m² & 400 g|m² felt-backed Broadloom.