



Product Specifications			
Collection		Scape Collection	
Description		Patterned Textured Loop Pile Carpet	
Pile Fibre		100% Econyl Regenerated Nylon	
Dye Method		Solution Dyed	
Method of Manufacture		Tufted	
Machine Gauge		1 10 th	
Pile Weight		1,050 g m ²	
Tuft Density		150,100 m ²	
Lead Time		Ex-Stock 2 Weeks Ex-Production 4-6 Weeks	
Format		Tiles (bitBAC)	Acoustic Tiles (feltBAC-NRB)
Pile Height		5.0 mm	5.0 mm
Total Thickness		9.7 mm	13.0 mm
Total Weight		5,210 g m ²	5,430 g m ²
Product Size		500 mm x 500 mm	500 mm x 500 mm
Pack Size		16 Tiles 4 m ² per box	12 Tiles 3 m ² per box
Availability		Stocked	Made-To-Order
Minimum Order Quantity		1 box 4 m ²	200 m ²
Recommended Laying Pattern		<i>Kota & Creole</i>	Monolithic
		<i>Parian</i>	Monolithic Quarter Turn
Installation Method		Loose-Lay on Tackifier	Loose-Lay on Tackifier
Recommended Adhesives		<i>F Ball & Co</i>	F41
		<i>Uzin</i>	U2100 Universal Tackifier

Performance Specifications			
Format		Tiles (bitBAC)	Acoustic Tiles (feltBAC-NRB)
Wear Rating		<i>EN 1307</i>	33 Heavy Commercial Use
Castor Chair Rating		<i>EN 985</i>	≥ 2.4r Continuous Use
Flammability Rating		<i>EN 13501-1:2020</i>	B _{FL} S1
Impact Sound Insulation		<i>EN ISO 10140</i>	ΔLw 27 dB
Sound Absorption		<i>EN ISO 11654</i>	α _w 0.25
Thermal Resistance		<i>EN 12667:2001</i>	< 0.17 m ² kW Suitable for UFH
Electrostatic Properties		<i>EN ISO 6356</i>	≤ 2 kV Antistatic
Colourfastness to Light		<i>ISO EN 105-B02</i>	> 7 (on a scale of 1-8)
Formaldehyde Emissions		<i>EN 717-1:2005</i>	Class E1
VOC Emissions		<i>Prodis-GUT</i>	GUT Certificate 14E008A4
		<i>BREEAM GN22 v2.3 2018</i>	Meets Exemplary Criteria
EPD		<i>ISO 14025 EN 15804</i>	EPD-BAL-20170200-EN
Certified Environmental Profile		<i>BRE Global</i>	ENP-499 dh-dj
LEED v.4 Compliance		<i>Potential Credits</i>	Materials & Resources
			Indoor Environmental Quality