



SHIMMER

Product Specification

Issue 2020.v1



Product Specifications			
Collection	Tussah Collection		
Description	Cut Pile Carpet		
Pile Fibre	100% Antron Nylon		
Dye Method	Continuous Dyed		
Method of Manufacture	Tufted		
Pile Weight	1,350 g m ²		
Tufts per m ²	215,000 m ²		
Lead Time	Ex-Stock 2 Weeks Ex-Production 3-6 Weeks		
Format	Planks (feltBAC-L)	Broadloom (webTEX)	
Backing	120 g m ² Felt + Pre-Applied Tackifier	Woven Synthetic Textile	
Pile Height	9.0 mm	9.0 mm	
Total Thickness	11.0 mm	11.0 mm	
Total Weight	2,920 g m ²	2,520 g m ²	
Product Size	1000 mm x 250 mm	4 m	
Pack Size	12 Planks 3 m ² per box	Std Roll Length +/-25 lm	
Availability	Stocked	Stocked	
Minimum Order Quantity	1 box 3 m ²	20 m ²	
Laying Pattern	Half Drop		
Installation Method	Loose-Lay	Direct Stick Double Stick Tensioned	
Recommended Adhesives	F Ball & Co	F3 F30	
	Uzin	Adhesive is Pre-Applied UZ 57 KE 2560	

Performance Specifications			
Format		Planks (feltBAC-L)	Broadloom (webTEX)
Wear Rating	EN 1307	31 Moderate Commercial Use	31 Moderate Commercial Use
Flammability Rating	EN 13501-1:2020	B _{F1} S1	C _{F1} S1
Impact Sound Insulation	EN ISO 10140	ΔL _w 31 dB	ΔL _w 31 dB
Thermal Resistance	EN 12667:2001	0.12 m ² kW Suitable for UFH	0.11 m ² kW Suitable for UFH
Electrostatic Properties	EN ISO 6356	≤ 2 kV Antistatic	≤ 2 kV Antistatic
Colourfastness	ISO 105-B02 Light	≥ 5 (scale of 1-8)	≥ 5 (scale of 1-8)
	ISO 105-X12 Rubbing	≥ 4 (scale of 1-5)	≥ 4 (scale of 1-5)
	ISO 105-E01 Water	≥ 4 (scale of 1-5)	≥ 4 (scale of 1-5)
VOC Emissions	Indoor Air Comfort	GUT Prodis Certified	GUT Prodis Certified
	BREEAM GN22 v2.3 2018	Meets Exemplary Criteria	Meets Exemplary Criteria
EPD	ISO 14025 EN 15804	EPD-VET-20170128-CBC1-DE	EPD-VET-20180174-CBC1-DE

Additional Information

Tussah Collection planks are supplied with tackifier adhesive pre-applied to the back of the modules. No additional adhesive is required. These planks must be installed with great care, to avoid trapping pile between the joints, which will result in visible seams. Once installed the planks should only be uplifted and relaid by an experienced floorlayer. Due to the construction of our Tussah Collection products and the need to take great care during fitting, the planks are likely to take longer to install than a traditional carpet tile, and this should be considered when planning an installation.

For a minimum quantity of 350 m² this product can also be supplied as 450 g|m² or 900 g|m² felt-backed Acoustic Broadloom.