

Product Specifications

<i>Description</i>		Woven Contract Bouclé		
<i>Pile Fibre</i>		100% Nylon		
<i>Dye Method</i>		Continuous Dyed		
<i>Method of Manufacture</i>		Woven		
<i>Pile Weight</i>		785 g m ²		
<i>Lead Time</i>		Ex-Stock 2 Weeks Ex-Production 4-6 Weeks		
<i>Format</i>		Tiles (feltBAC feltBAC-Z)	Broadloom (texBAC-FW)	Acoustic B'loom (feltBAC-FW)
<i>Backing</i>		350 g m ² Recycled Felt	Woven Synthetic Textile	800 g m ² Recycled Felt
<i>Pile Height</i>		2.0 mm	2.0 mm	2.0 mm
<i>Total Thickness</i>		5.0 mm	3.5 mm	8.0 mm
<i>Total Weight</i>		2,955 g m ²	2,200 g m ²	2,755 g m ²
<i>Product Size</i>		480 mm x 480 mm	4 m	4 m
<i>Pack Size</i>		22 Tiles 5.07 m ² per box	Std Roll Length +/-28 lm	Std Roll Length +/-20 lm
<i>Availability</i>		Stocked	Stocked	Made-to-Order
<i>Minimum Order Quantity</i>		10 boxes 50.70 m ²	20 m ²	400 m ²
<i>Laying Pattern</i>	<i>feltBAC Tiles</i>	Quarter Turn		
	<i>feltBAC-Z Tiles</i>	Monolithic Ashlar		
<i>Installation Method</i>		Loose-Lay on Tackifier	Direct Stick (Permanent)	Direct Stick (Permanent)
<i>Recommended Adhesives</i>	<i>F Ball</i>	F41	F3 F30	F3 F30
	<i>Uzin</i>	Universal Tackifier	UZ 57 KE 2560	KE 2560

Performance Specifications

<i>Format</i>		Tiles (feltBAC feltBAC-Z)	Broadloom (texBAC-FW)	Acoustic B'loom (feltBAC-FW)
<i>Wear Rating</i>	<i>EN 1307</i>	33 Heavy Commercial Use	33 Heavy Commercial Use	33 Heavy Commercial Use
<i>Flammability Rating</i>	<i>EN 13501-1:2020</i>	C _{FL} S1	C _{FL} S1	C _{FL} S1
<i>Impact Sound Insulation</i>	<i>EN ISO 10140</i>	ΔLw 18 dB	ΔLw 17 dB	ΔLw 26 dB
<i>Sound Absorption</i>	<i>EN ISO 11654</i>	αw 0.20	αw 0.15	αw 0.10
<i>Thermal Resistance</i>	<i>EN 12667:2001</i>	0.1 m ² kW Suitable for UFH	0.1 m ² kW Suitable for UFH	
<i>Electrostatic Properties</i>	<i>EN ISO 6356</i>	≤ 2.0 kV Antistatic	≤ 2 kV Antistatic	≤ 2 kV Antistatic
<i>VOC Emissions</i>	<i>Indoor Air Comfort</i>	Gold	Gold	Gold
	<i>BREEAM GN22 v2.3 2018</i>	Meets Exemplary Criteria	Meets Exemplary Criteria	Meets Exemplary Criteria
<i>EPD</i>	<i>ISO 14025 EN 15804</i>	BEN-20170207-CBD1-EN	BEN-20160108-CBC1-EN	
<i>Declaration of Performance</i>	<i>EN 14041</i>	2531-CPR-CXA10218	2531-CPR-CXA10134	2531-CPR-CXA10115

Additional Information

For a minimum quantity of 40 boxes (202.80 m²) this product can be supplied in the following sizes: 240mmx960mm, 480mmx960mm, 960mmx960mm.

Standard 480mm x 480mm tiles should be installed Quarter Turn. For a monolithic appearance we recommend our interlocking tiles (feltBAC-Z) which feature an innovative zigzag-cut leading and trailing edge; feltBAC-Z tiles are available to order for a minimum quantity of 10 boxes (50.07 m²). Please consider your preferred laying pattern carefully when specifying tiles.

For a minimum quantity of 400 m² this product can also be supplied as 300 g|m² or 400 g|m² felt-backed Broadloom.