



Product Specifications

<i>Description</i>		Patterned Textured Loop Pile Carpet	
<i>Pile Fibre</i>		100% Econyl Regenerated Nylon	
<i>Dye Method</i>		Continuous Dyed	
<i>Method of Manufacture</i>		Tufted	
<i>Machine Gauge</i>		1 12 th	
<i>Pile Weight</i>		770 g m ²	
<i>Tuft Density</i>		197,400 m ²	
<i>Lead Time</i>		Ex-Stock 2 Weeks Ex-Production 4-6 Weeks	
<i>Format</i>		Tiles (bitBAC)	Acoustic Tiles (feltBAC-NRB)
<i>Pile Height</i>		3.4 mm	3.8 mm
<i>Total Thickness</i>		6.8 mm	9.7 mm
<i>Total Weight</i>		4,365 g m ²	4,570 g m ²
<i>Product Size</i>		500 mm x 500 mm	500 mm x 500 mm
<i>Pack Size</i>		20 Tiles 5 m ² per box	12 Tiles 3 m ² per box
<i>Availability</i>		Stocked	Made-To-Order
<i>Minimum Order Quantity</i>		1 box 5 m ²	200 m ²
<i>Recommended Laying Pattern</i>		Brick	Brick
<i>Installation Method</i>		Loose-Lay on Tackifier	Loose-Lay on Tackifier
<i>Recommended Adhesives</i>		<i>F Ball & Co</i> F41	F41
		<i>Uzin</i> U2100 Universal Tackifier	Universal Tackifier

Performance Specifications

<i>Format</i>		Tiles (bitBAC)	Acoustic Tiles (feltBAC-NRB)
<i>Wear Rating</i>	<i>EN 1307</i>	33 Heavy Commercial Use	33 Heavy Commercial Use
<i>Castor Chair Rating</i>	<i>EN 985</i>	≥ 2.4r Continuous Use	≥ 2.4r Continuous Use
<i>Flammability Rating</i>	<i>EN 13501-1:2020</i>	B _{F1} S1	C _{F1} S1
<i>Impact Sound Insulation</i>	<i>EN ISO 10140</i>	ΔLw 25 dB	ΔLw 32 dB
<i>Sound Absorption</i>	<i>EN ISO 11654</i>	αw 0.20	αw 0.30
<i>Thermal Resistance</i>	<i>EN 12667:2001</i>	< 0.17 m ² kW Suitable for UFH	
<i>Electrostatic Properties</i>	<i>EN ISO 6356</i>	≤ 2 kV Antistatic	≤ 2 kV Antistatic
<i>Colourfastness to Light</i>	<i>ISO EN 105-B02</i>	> 6 (on a scale of 1-8)	> 6 (on a scale of 1-8)
<i>Formaldehyde Emissions</i>	<i>EN 717-1:2005</i>	Class E1	Class E1
<i>VOC Emissions</i>		<i>Prodis-GUT</i>	GUT Certified
		<i>BREEAM GN22 v2.3 2018</i>	Meets Exemplary Criteria
<i>EPD</i>	<i>ISO 14025 EN 15804</i>	EPD-BAL-20150280-EN	EPD-BAL-20180018-EN
<i>Certified Environmental Profile</i>	<i>BRE Global</i>	ENP-499 de-dg	ENP-499 dz-eb
<i>LEED v.4 Compliance</i>		<i>Potential Credits</i>	
		Materials & Resources	Materials & Resources
		Indoor Environmental Quality	Indoor Environmental Quality

Additional Information

Standard colours are available as Acoustic Tiles for a minimum order quantity of 200m². For non-standard colours the minimum quantity is 600m².