

**Product Specifications**

Collection	Runic Collection		
Description	Cut Pile Loose-Lay Rug		
Pile Fibre	100% Type 6 Nylon		
Dye Method	Continuous Dyed		
Method of Manufacture	Tufted		
Machine Gauge	1 10 th		
Pile Weight	1,950 g m ²		
Tuft Density	228,500 m ²		
Pile Height	16.0 mm		
Total Thickness	17.0 mm		
Total Weight	2,800 g m ²		
Lead Time	Ex-stock 3 weeks Ex-production 5 weeks		
Format	Rugs (lamBAC)	Sheet (lamBAC)	
Backing	Laminate Backing	Laminate Backing	
Product Size	Made-To-Measure	4 m Rolls	
Availability	Made-To-Order	Stocked	
Minimum Order Quantity	1 Rug	20 m ²	
Installation Method	Loose-Lay	Loose-Lay	

Performance Specifications

Wear Class	EN 1307	31 Moderate Commercial Use
Flammability Rating	EN 13501	E _{FL}
Impact Sound Reduction	ISO 8302	ΔLw 28 dB
Thermal Insulation	ISO 6356	0.14 m ² kW Suitable for UFH
Electrostatic Properties	EN ISO 10140	≤ 2 kV Antistatic

Additional Information

This product is designed for use as a rug. The unique Laminate Backing is non-slip and requires no adhesive. Furthermore when cut, the edges need no additional binding or sealing. It is supplied as a made-to-order rug or in sheet format for cutting to shape & size on site. It is not designed for wall-to-wall installation whether that be direct stick, double stick or tensioned.