



Product Specifications		
Format		clicBAC
Collection		Essence Collection
Description		Commercial Cork Flooring
Construction	Wear Layer	Xtramatt+ UV Lacquer
	Decorative Layer	Cork Veneer
	Comfort Layer	Agglomerated Cork
	Core	High Density Fibreboard + 2G
	Underlay	Integrated Cork Underlay
Total Thickness		10.5 mm
Product Size		905 mm x 295 mm
Pack Size		8 Planks 2.136 m ²
Availability		Stocked
Minimum Order Quantity		1 Box 2.136 m ²
Installation Method	Standard:	Floating: Fold & Click
	Optional:	Glue Down: Fold, Click & Glue
Recommended Adhesives		Wakol MS 260 ^{*1}
Lead Time		Ex-Stock 3 Weeks Ex-Production 6-8 Weeks

Performance Specifications		
Format		clicBAC
Wear Rating	EN 1307	31 Moderate Commercial Use
Effect of Furniture Leg	ISO 16581 EN 424	No Visible Change or Damage
Residual Indentation	EN ISO 24343-1	≤ 0.40 mm
Flammability Rating	EN 13501-1:2020	C _{FL} S1
Impact Sound Insulation	EN ISO 10140	ΔLw 16 dB
	EN 13893:2003	Class DS
	BS 7976-2:2002 — Dry	μ 0.63 Low Slip Potential
Slip Resistance	BS 7976-2:2002 — Wet	μ 0.42 Low Slip Potential
Formaldehyde Emissions	EN 717-1	E1
Content of Pentachlorophenol (PCP)	EN 14041 Annex B	Undetectable
Thermal Resistance	EN 12667:2001	0.15 m ² kW Suitable for UFH
Stain Resistance	EN 438-2 Group 1 Only 10 min	Grade 5 No Change
VOC Emissions	TÜV Proficert	Premium Meets BREEAM Exemplary Criteria
EPD	ISO 14025 EN 15804	EPD-AMO-20150178-IBA1-EN
BREEAM Potential Credits	Indoor Air Quality	1 to 5
	Environmental Product Declaration	1
	Designing for Durability and Resilience	1
	Material Efficiency	1
LEED v.4 Potential Credits	Environmental Product Declaration	1 to 2
	Low-Emitting Materials	1 to 3
	Indoor Air Quality Assessment	1 to 2

*1 For Wakol suppliers in the UK please visit <https://lecoluk.com/distributors-wakol/>