

FORMAT		CORKFORM clicBAC
Collection		Climate ⁺ Collection
Description		Commercial Cork Flooring
Construction	Wear Layer	PVC-Free UV Cured Polyurethane
	Decorative Layer	Cork Veneer
	Sub-surface	Agglomerated Cork
	Core	Stabilised Cork Composite + 2G Locking System
	Underlay	Integrated Cork Underlay
Water Resistance		Waterproof ^{*1}
Total Thickness		7.0 mm
Edge Finish		Micro-bevel on all 4 sides
Product Size		1225 mm x 190 mm
Pack Size		8 Planks 1.862 m ²
Availability		Stocked in the EU
Lead Time		Stock 2-3 weeks Prod 6-8 weeks
Minimum Order Quantity		1 Box 1.862 m ²
Installation Method	Standard	Floating: Fold & Click
	Optional	Glue Down: Fold, Click & Glue
Recommended Adhesives		Wakol MS260 ^{*2}
Recommended Joint Sealer		Unika ClicSeal
Recommended Gap Filler		Unika Colour Sealant

PERFORMANCE SPECIFICATIONS		
Wear Rating	EN 1307	33 Heavy Commercial Use
Castor Chair Resistance	EN 425	≥ 2.4r Continuous Use
Effect of Furniture Leg	ISO 16581 EN 424	No Visible Change or Damage
Impact Resistance	EN 13329:2006	≥ 1600
Flammability Rating	EN 13501-1:2020	B _{FL} S1
Impact Sound Insulation	EN ISO 10140	ΔL _w 18 dB
	EN 13893:2003	Class DS
	BS 7976-2:2002 Dry	μ 0.67 Low Slip Potential
	BS 7976-2:2002 Wet	μ 0.54 Low Slip Potential
Formaldehyde Emissions	EN 717-1	E1
Content of Pentachlorophenol (PCP)	EN 14041 Annex B	Undetectable
Underfloor Heating		Compatible with most wet UFH systems
Stain Resistance	EN 438-2	Grade 5 No Change
VOC Emissions	TÜV Proficert	Premium
	BREEAM GN22	BREEAM Exemplary

BREEAM & LEED		
BREEAM Available Credits	Indoor Air Quality	1 to 5
	Design for Durability and Resilience	1
	Material Efficiency	1
LEED v.4 Available Credits	Low-Emitting Materials	1 to 3
	Indoor Air Quality Assessment	1 to 2

^{*1} Not suitable for permanently wet areas

^{*2} Wakol MS260 is available to purchase from Quadrant. For additional suppliers in the UK please visit <https://lecoluk.com/distributors-wakol/>