

FORMAT		clicBAC
Collection		Essence Collection
Description		Commercial Cork Flooring
Construction	Wear Layer	Xtramatt+ UV Lacquer
	Decorative Layer	Cork Veneer
	Comfort Layer	Agglomerated Cork
	Core	High Density Fibreboard + 2G Locking System
	Underlay	Integrated Cork Underlay
Water Resistance		Not Waterproof* ¹
Total Thickness		10.5 mm
Product Size		905 mm x 295 mm
Pack Size		8 Planks 2.136 m ²
Availability		Stocked in the EU
Lead Time		Stock 2-3 weeks Prod 6-8 weeks
Minimum Order Quantity		1 Box 2.136 m ²
Installation Method	Standard	Floating: Fold & Click
	Optional	Glue Down: Fold, Click & Glue
Recommended Adhesives		Wakol MS260* ²
Recommended Joint Sealer		Unika ClicSeal
Recommended Gap Filler		Unika Colour Sealant
PERFORMANCE SPECIFICATIONS		
Wear Rating	EN 1307	31 Moderate Commercial Use
Effect of Furniture Leg	ISO 16581 EN 424	No Visible Change or Damage
Residual Indentation	EN ISO 24343-1	≤ 0.40 mm
Flammability Rating	EN 13501-1:2020	C _{FL} S1
Impact Sound Insulation	EN ISO 10140	ΔL _w 16 dB
Slip Resistance	EN 13893:2003	Class DS
	BS 7976-2:2002 — Dry	μ 0.63 Low Slip Potential
	BS 7976-2:2002 — Wet	μ 0.42 Low Slip Potential
Formaldehyde Emissions	EN 717-1	E1
Content of Pentachlorophenol (PCP)	EN 14041 Annex B	Undetectable
Thermal Resistance	EN 12667:2001	0.15 m ² kW Suitable for UFH
Stain Resistance	EN 438-2 Group 1 Only 10 min	Grade 5 No Change
VOC Emissions	TÜV Proficert	Premium Meets BREEAM Exemplary Criteria
EPD	ISO 14025 EN 15804	EPD-AMO-20150178-IBA1-EN
BREEAM & LEED		
BREEAM Available Credits	Indoor Air Quality	1 to 5
	Environmental Product Declaration	1
	Designing for Durability and Resilience	1
	Material Efficiency	1
LEED v.4 Available Credits	Environmental Product Declaration	1 to 2
	Low-Emitting Materials	1 to 3
	Indoor Air Quality Assessment	1 to 2

*¹ If this product is to be used in areas subject to wetting or spillage the joints must be sealed with joint sealant

*² Wakol MS260 is available to purchase from Quadrant. For additional suppliers in the UK please visit <https://lecoluk.com/distributors-wakol/>