



SALTO 55

Product Specification

Issue 2020.v1



Product Specifications			
Description		Commercial Loose-Lay LVT Flooring	
Surface Construction	Wear Layer	0.55 mm PU Wear Layer	
	Decorative Layer	High Resolution Print Film	
Availability		Stocked	
Lead Time		Ex-stock 1-2 wks Ex-production 8-10 wks	
Format		hardBAC	hardBAC-NR (Acoustic Backing)
Backing Construction	Core	Stabilised hardBAC Core	Stabilised hardBAC Core
	Attached Underlay		Attached Acoustic Underlay
Total Thickness		5.0 mm	5.0 mm
Total Weight		8,100 g m ²	6,400 g m ²
Product Size	Tiles	457.2 mm x 457.2 mm	
		500 mm x 500 mm	500 mm x 500 mm
		914.4 mm x 914.4 mm	914.4 mm x 914.4 mm
	Planks	1200 mm x 180 mm	1200 mm x 180 mm
Pack Size	Tiles	10 Tiles 2.5 m ²	10 Tiles 2.5 m ²
	Planks	10 Planks 2.16 m ²	10 Planks 2.16 m ²
Minimum Order Quantity		1 Box	1 Box
Installation Method		Loose-lay on Tackifier	Loose-lay on Tackifier
Recommended Laying Pattern	Tiles	Monolithic	Monolithic
	Planks	Variable Drop	Variable Drop
Recommended Adhesives	F Ball & Co	F41	F41
	Uzin	U2100 Universal Tackifier	U2100 Universal Tackifier

Performance Specifications			
Format		hardBAC	hardBAC-NR (Acoustic Backing)
Wear Rating	EN 1307	33 Heavy Commercial Use	33 Heavy Commercial Use
Castor Chair Resistance	EN 425	≥ 2.4r Continuous Use	≥ 2.4r Continuous Use
Residual Indentation	EN 24343	≤ 0.1 mm	≤ 0.2 mm
Flammability Rating	EN 13501-1:2020	B _{F1} S1	B _{F1} S1
Impact Sound Insulation	EN ISO 10140	ΔL _w 7 dB	ΔL _w 19 dB
Slip Resistance	EN 13893:2003	Class DS	Class DS
	BS 7976-2:2002 Dry	μ 0.78 Low Slip Potential	μ 0.78 Low Slip Potential
	BS 7976-2:2002 Wet	μ 0.48 Low Slip Potential	μ 0.48 Low Slip Potential
	DIN 51130	R9	R9
Thermal Resistance	EN 12667:2001	0.17 m ² kW Suitable for UFH	0.39 m ² kW Suitable for UFH
Electrostatic Properties	EN ISO 6356	≤ 2 kV Antistatic	≤ 2 kV Antistatic
Colourfastness to Light	ISO EN 105-B02	> 6 (on a scale of 1-8)	> 6 (on a scale of 1-8)
Formaldehyde Emissions	EN 717-1	E1	E1
Content of Pentachlorophenol (PCP)	EN 14041 Annex B	Undetectable	Undetectable
VOC Emissions	Indoor Air Comfort	Gold Breeam, LEED & Ska Compliant	Gold Breeam, LEED & Ska Compliant
EPD	ISO 14025 EN 15804	SCS-03633	SCS-03633

Additional Information

hardBAC-NR Acoustic Tiles & Planks are only available in selected colours. For further information please contact Customer Services.